

# 59LF-P Series

Bronze Wye-Strainer

## LEAD FREE



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

### DESCRIPTION

The lead free\* APOLLOPUSH™ 59LF Series Strainers with Quick Push Connections are designed to protect potable water systems from unwanted foreign particles with minimum pressure loss. The valves are built for long reliable service with proven ASTM grade materials including a lead free\* bronze body and a large area stainless steel screen.

### FEATURES

- Quick Push End Connection "Push to Connect" Installation
- APOLLOPUSH™ Incorporates Proven TECTITE™ Technology
- Direct Connectors are Permanently Installed
- Self-Aligning Screen Design
- Pushed Connections are Removable Using Optional Demounting Tool
- Standard Valve:(01) Plain Cap 50 Mesh (1/2"), 20 Mesh (3/4", 1")
- Blow-Off Ball Valve Option
- 100% Cast, Machined and Assembled in the USA - ARRA Compliant

### PERFORMANCE RATING

- Working Pressure (non-shock): Maximum Pressure: 200 psi (17.2 bar)
- Maximum Temperature: 250°F (121°C)

### APPROVALS

- ASSE 1061-2006 - Push Fitting Performance Requirements
- IAPMO IGC 188 (UPC) Compliant for CU/CPVC/PEX/PE-RT
- CRN OE8959.5
- NSF/ANSI 61 Water Quality
- NSF/ANSI 372 Lead Free
- PE-RT - ASTM F2769 using EPC PEX Inserts

### STANDARD MATERIALS LIST

<b>BODY</b>	ASTM B584 C89836 Bronze
<b>CAP</b>	C27451 Lead Free Brass
<b>CONNECTOR HOUSING</b>	C27451 Lead Free Brass
<b>CONNECTOR SLEEVE</b>	Acetal Copolymer
<b>CONNECTOR RETAINER</b>	316 Stainless Steel
<b>CONNECTOR O-RING</b>	NSF grade EPDM
<b>SCREEN</b>	302 Stainless Steel
<b>O-RING</b>	Teflon
<b>GASKET</b>	PTFE

### DIMENSIONS

APOLLO PART NUMBER	EPC PART NUMBER	EPC MODEL NUMBER	SIZE (IN.)	LENGTH (IN.)	CV	WT. (LB.)
59LF-003-01P	10177538	230	1/2"	4.9	5	.75
59LF-004-01P	10177541	230	3/4"	6.2	15	1.7
59LF-005-01P	10177543	230	1"	7.5	28	2.7

*For liquids the flow coefficient - Cv - expresses the flow capacity in gallons per minute (GPM) of 60°F water with a pressure drop of 1 psi (lb/in<sup>2</sup>).*

### OPTIONAL DEMOUNT TOOLS

SIZE	APOLLO PART NUMBER	EPC PART NUMBER
1/2"	D514500	10165630
3/4"	D514800	10165625
1"	D515100	10165627



\*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law 111-380. ANSI 3rd party approved and listed.