

59LF Series

Model YB-LF - Bronze Wye-Strainer

LEAD FREE





| Job Name: | |
|------------------|--|
| Job Location: | |
| Engineer: | |
| Contractor: | |
| Tag: | |
| PO#: | |
| Rep: | |
| Wholesale Dist.: | |

DESCRIPTION

The **Apollo* Lead Free* YB-LF (59LF) Series Heavy Pattern Strainers** are designed with large area screens to protect piping systems and process equipment from unwanted foreign particles with minimum pressure loss.

FEATURES

- · Lead Free*
- 100% Factory Pressure Tested
- Removable Self-Aligning Screen Design
- Numerous Mesh and Blow-off Options including Blow-off Ball Valves
- ARRA Compliant
- 100% Cast, Machined and Assembled in the USA

MODELS

- (59LF000) Female NPT Connection
- (59LF300) Solder Connection (1/2"-3")
- (59LF400) FNPT Inlet X Male NPT Out (3/4"-1")

APPROVALS

- NSF/ANSI 372 Lead Free
- CRN-0E 8959.5

PERFORMANCE RATING

- Working Pressure: CWP: 400 psi SWP: 125 psi
- Maximum Temperature: 353°F

OPTIONS

- (-E1) 20 Mesh
- (-01) Plain Cap
- (-B1) 60 Mesh
- (-C1) 80 Mesh
- (-H1) 100 Mesh
- (-02) Tapped Cap
- (-P2) Tapped Cap with Plug
- (-06) Tapped cap with Ball Valve (3/4" 2" Only)

STANDARD MATERIALS LIST

| BODY | Cast Bronze, ASTM Lead Free B584 | | | |
|----------------------|--|--|--|--|
| САР | Lead Free Bronze, UNS C27451 (1/8" - 1") Lead Free Bronze, ASTM B584 C89836 (1-1/4" - 4") | | | |
| SCREEN | Stainless Steel, 304 | | | |
| O-RING (1-8" - 1/2") | PTFE | | | |
| GASKET (3/4" - 4") | PTFE | | | |

DIMENSIONS

| MODEL PART | | SIZE | LENGTH (IN.) | | CAP TAPPING | NET SCREEN | WT. |
|------------|-------------|-------|--------------|------|--------------|------------|-------|
| NUMBER | NUMBER | (IN.) | FNPT | MNPT | (-02 SUFFIX) | AREA (IN²) | (LB.) |
| YB18LF | 59LF-000-01 | 1/8 | 2 | NA | 1/8 NPT | 2.3 | .44 |
| YB14LF | 59LF-001-01 | 1/4 | 2 | NA | 1/8 NPT | 2.3 | .42 |
| YB38LF | 59LF-002-01 | 3/8 | 2.69 | NA | 1/4 NPT | 3.2 | .78 |
| YB12LF | 59LF-003-01 | 1/2 | 2.69 | NA | 1/4 NPT | 3.2 | .75 |
| YB34LF | 59LF-004-01 | 3/4 | 4.25 | NA | 1/2 NPT | 6.7 | 1.7 |
| YB1LF | 59LF-005-01 | 1 | 4.75 | NA | 3/4 NPT | 10.8 | 2.7 |
| YB114LF | 59LF-006-01 | 1-1/4 | 5.13 | NA | 3/4 NPT | 13.5 | 3.4 |
| YB112LF | 59LF-007-01 | 1-1/2 | 5.75 | NA | 1 NPT | 19.0 | 5.3 |
| YB2LF | 59LF-008-01 | 2 | 6.66 | NA | 1-1/4 NPT | 27.6 | 7.2 |
| YB212LF | 59LF-009-01 | 2-1/2 | 8.24 | NA | 1-1/4 NPT | 41.0 | 11.3 |
| YB3LF | 59LF-010-01 | 3 | 9 | NA | 1-1/2 NPT | 56.0 | 15.5 |
| YB4LF | 59LF-011-01 | 4 | 11.92 | NA | 1-1/2 NPT | 98.0 | 30.7 |
| 59LF-400 | | | | | | | |
| YBM34LF | 59LF-404-01 | 3/4 | NA | 4.25 | 1/2 NPT | 6.7 | 1.7 |
| YBM1LF | 59LF-405-01 | 1 | NA | 4.75 | 3/4 NPT | 10.8 | 2.7 |

Model number and part number shown are for FNPT connections.

STANDARD SCREENS

| SIZE (IN.) | SCREEN | | | |
|------------|------------------|--|--|--|
| 1/8 to 1/2 | 50 Mesh | | | |
| 3/4 to 3 | 20 Mesh | | | |
| 4 | .125 Perforation | | | |

*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law 111-380. ANSI 3rd party approved and listed.





59LF SeriesModel YB-LF - Bronze Wye-Strainer

LEAD FREE

FLOW CURVES







